

Page 1/15

Printing date 02/27/2024

Reviewed on 02/26/2024

1 Identification

· Product identifier

· Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

· Article number: HFP360

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: HIGH TECK PRODUCTS PO BOX 24631 WEST PALM BEACH, FLORIDA 33416 USA 877-900-8325

info@highteckproducts.com

· Information department: Product safety department

Emergency telephone number: 800 424-9300 (Chemtrec)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.

Substances and mixtures which, in contact with water, emit flammable gases 2

H261 In contact with water releases flammable



GHS08 Health hazard

Germ Cell Mutagenicity 1B

Carcinogenicity 1B H350 May cause cancer.

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the

unborn child.

H340 May cause genetic defects.



Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07

· **Signal word** Danger

· Hazard-determining components of labeling:

acetone

Naphtha (petroleum), hydrotreated heavy

toluene

n-butyl acetate

Hazard statements

Highly flammable liquid and vapor.

In contact with water releases flammable gas.

Causes serious eye irritation.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not allow contact with water.

Handle under inert gas. Protect from moisture.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, sand, extinguishing powder to extinguish.

Store in a dry place. Store in a closed container.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

(Contd. of page 2)

- · Classification system:
- NFPA ratings (scale 0 4)



The substance demonstrates unusual reactivity with water.

· HMIS-ratings (scale 0 - 4)



*2 Health = *2 3 Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
67-64-1	acetone	25-50%
123-86-4	n-butyl acetate	25-50%
1330-20-7	xylene	2.5-10%
7429-90-5	aluminium	≤2.5%
64742-48-9	Naphtha (petroleum), hydrotreated heavy	≤2.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤2.5%
100-41-4	ethylbenzene	0-≤2.5%
108-88-3	toluene	0-≤2.5%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

(Contd. of page 3)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Extinguishing powder. Do not use water.

CO2. Do not use water.

Sand. Do not use water.

Special powder for metal fires. Do not use water.

CO2, sand, extinguishing powder. Do not use water.

- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:		
67-64-1	acetone	200 ppm
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m
100-41-4	ethylbenzene	33 ppm
71-36-3	B butan-1-ol	60 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
108-88-3	toluene	67 ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	18 mg/m³
64-17-5	ethanol	1,800 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
7664-38-2	phosphoric acid	3 mg/m³
67-56-1	methanol	530 ppm
67-63-0	propan-2-ol	400 ppm
PAC-2:		<u>'</u>
67-64-1	acetone	3200* ppm

(Contd. on page 5)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

		(Contd. of page
	n-butyl acetate	200 ppm
1330-20-7		920* ppm
	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ²
	ethylbenzene	1100* ppm
	butan-1-ol	800 ppm
	2-methoxy-1-methylethyl acetate	1,000 ppm
108-88-3	toluene	560 ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	200 mg/m³
64-17-5	ethanol	3300* ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
7664-38-2	phosphoric acid	30 mg/m³
67-56-1	methanol	2,100 ppm
67-63-0	propan-2-ol	2000* ppm
· PAC-3:		
67-64-1	acetone	5700* ppm
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
100-41-4	ethylbenzene	1800* ppm
71-36-3	butan-1-ol	8000** ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
108-88-3	toluene	3700* ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	1,200 mg/m³
64-17-5	ethanol	15000* ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
7664-38-2	phosphoric acid	150 mg/m³
67-56-1	methanol	7200* ppm
67-63-0	propan-2-ol	12000** ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

(Contd. on page 6)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

(Contd. of page 5)

- Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

	4-1 acetone	
PEL	Long-term value: 2400 mg/m³, 1000 ppm	
REL	Long-term value: 590 mg/m³, 250 ppm	
TLV	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI	
123-	86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm	
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm	
TLV	Short-term value: 150 ppm Long-term value: 50 ppm	
1330	-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm BEI, A4	
100-	41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm OTO, BEI, A3	
108-	88-3 toluene	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	
REL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm BEI, OTO, A4	

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

(Contd. of page 6)

· Ingredients with biological limit values:

67-64-1 acetone

BEI 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. (Contd. on page 8)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

(Contd. of page 7)

Due to missing tests no recommendation to the glove material can be given for the product, the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

9 Physic	al and	chemi	cal	pro	oerti	es
----------	--------	-------	-----	-----	-------	----

· Information on I	basic phy	/sical and	chemical	properties
<u> </u>	4 -			

· General Information

· Appearance:

Form: Liquid Color: Silver

Characteristic · Odor: · Odor threshold: Not determined.

· pH-value: Not determined (pH N/A in solvent coatings)

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 55.8-56.6 °C (132.4-133.9 °F)

· Flash point: <-18 °C (<-0.4 °F)

· Flammability (solid, gaseous): Highly flammable.

Contact with water liberates extremely flammable gases.

· Auto igniting: 370 °C (698 °F)

· Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

Product is not explosive. However, formation of explosive air/ · Danger of explosion:

vapor mixtures are possible.

· Explosion limits:

Lower: 1.2 Vol % Upper: 13 Vol %

· Vapor pressure at 20 °C (68 °F): 233 hPa (174.8 mm Hg) · Vapor pressure at 50 °C (122 °F): 800 hPa (600 mm Hg)

Density at 20 °C (68 °F): 0.9097 g/cm³ (7.5914 lbs/gal)

· Relative density Not determined.

· Vapor density Not determined.

(Contd. on page 9)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

	(Contd. of p	oage
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octano	ol/water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	80.9 %	
VOC content:	≥39.96-<40.03 %	
	607.1 g/l / 5.07 lb/gal	
Solids content:	24.3 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- Possibility of hazardous reactions Contact with water releases flammable gases.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:			
123-86-4 ı	123-86-4 n-butyl acetate			
Oral	LD50	13,100 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	>21 mg/l (rat)		

- Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

· Carcinogenic categories

1330-20-7 xylene

3

(Contd. on page 10)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

	(Co	ontd. of page 9)
100-41-4	ethylbenzene	2B
108-88-3	toluene	3
112926-00-8	Precipitated silica (Silica-Amorphous)	3
64-17-5	ethanol	1
67-63-0	propan-2-ol	3
· NTP (Nation	al Toxicology Program)	
None of the i	ngredients is listed.	
· OSHA-Ca (O	ccupational Safety & Health Administration)	
None of the ii	ngredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Not hazardous for water.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

4 Transport information	
· UN-Number	UN3148
DOT, IMDG, IATA	UN3146
· UN proper shipping name	
·DOT	Water-reactive liquid, n.o.s. (Aluminum powder)
· IMDG, IATA	WATER-REACTIVE LIQUID, N.O.S. (ALUMINIUM POWDER)
	(Contd. on page 1

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

(Contd. of page 10) · Transport hazard class(es) · DOT 4.3 Substances which, in contact with water, emit · Class flammable gases · Label 4.3 · IMDG, IATA · Class 4.3 Substances which, in contact with water, emit flammable gases · Label 4.3 · Packing group DOT, IMDG, IATA Ш · Environmental hazards: Not applicable. Warning: Substances which, in contact with water, · Special precautions for user emit flammable gases · Hazard identification number (Kemler code): 429 · EMS Number: F-G.S-N · Segregation groups (SGG15) Powdered metals Stowage Category Stowage Code SW2 Clear of living quarters. · Handling Code H1 Keep as dry as reasonably practicable SG26 In addition: from goods of classes 2.1 and 3 Segregation Code when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · DOT **Quantity limitations** On passenger aircraft/rail: 1 L On cargo aircraft only: 5 L · IMDG · Limited quantities (LQ) 500 ml · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 12)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

(Contd. of page 11)

· UN "Model Regulation":

UN 3148 WATER-REACTIVE LIQUID, N.O.S. (ALUMINIUM POWDER), 4.3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355	(extremely i	hazardous	substances)	:
---------------	--------------	-----------	-------------	---

None of the ingredients is listed.

Section 313	(Specific	r tovic ch	omical	lietinae).
Section 313	いっしんしいい	, luxic cii	ellilleal i	แอนเหนอ).

1330-20-7	xylene
7429-90-5	aluminiui

100-41-4 ethylbenzene

71-36-3 butan-1-ol

108-88-3 toluene

7664-38-2 phosphoric acid

67-56-1 methanol

67-63-0 propan-2-ol

· TSCA (Toxic Substances Control Act):

13CA (TOX	ic Substances Control Acty.	
67-64-1	acetone	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
9004-36-8	Cellulose Acetate Butyrate	ACTIVE
1330-20-7	xylene	ACTIVE
7429-90-5	aluminium	ACTIVE
64742-48-9	Naphtha (petroleum), hydrotreated heavy	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
100-41-4	ethylbenzene	ACTIVE
71-36-3	butan-1-ol	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
108-88-3	toluene	ACTIVE
64-17-5	ethanol	ACTIVE
108-83-8	2,6-dimethylheptan-4-one	ACTIVE
7664-38-2	phosphoric acid	ACTIVE
67-56-1	methanol	ACTIVE
8002-74-2	Paraffin waxes and Hydrocarbon waxes	ACTIVE
67-63-0	propan-2-ol	ACTIVE

· Hazardous Air Pollutants

1330-20-7	xylene
100-41-4	ethylbenzene
108-88-3	toluene
67-56-1	methanol

(Contd. on page 13)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

(Contd. of page 12) · Proposition 65 · Chemicals known to cause cancer: 100-41-4 ethylbenzene · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: 108-88-3 toluene 64-17-5 ethanol 67-56-1 methanol Carcinogenic categories · EPA (Environmental Protection Agency) 67-64-1 acetone 1330-20-7 xylene 100-41-4 ethylbenzene D 71-36-3 butan-1-ol D Ш

108-88-3	toluene	
· TLV (Threshold Limit Value)		
	acetone	
1330-20-7		
7429-90-5	aluminium	
400 44 4	- 4lex dle - a - a - a	

	<u> </u>		
7429-90-5	aluminium	A4	
100-41-4	ethylbenzene	A3	
108-88-3	toluene	A4	
64-17-5	ethanol	A3	
67-63-0	propan-2-ol	A4	

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

acetone

Naphtha (petroleum), hydrotreated heavy

toluene

n-butyl acetate

Hazard statements

Highly flammable liquid and vapor.

In contact with water releases flammable gas.

Causes serious eye irritation.

(Contd. on page 14)

A4 A4

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

(Contd. of page 13)

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not allow contact with water.

Handle under inert gas. Protect from moisture.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, sand, extinguishing powder to extinguish.

Store in a dry place. Store in a closed container.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Product Safety Dept.
- Date of preparation / last revision 02/27/2024
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 15)

Printing date 02/27/2024 Reviewed on 02/26/2024

Trade name: HFP360 SPARKLE SILVER H.O.K. B/C

HMIS: Hazardous Materials Identification System (USA)

(Contd. of page 14)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Substances and mixtures which, in contact with water, emit flammable gases 2: Substances and mixtures which in contact with water emit flammable gases - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Germ Cell Mutagenicity 1B: Germ cell mutagenicity - Category 1B

Carcinogenicity 1B: Carcinogenicity - Category 1B

Toxic to Reproduction 2: Reproductive toxicity - Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.