



Safety Data Sheet acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

1 Identification

- **Product identifier**
- **Trade name:** HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C
- **Article number:** HFP451C
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
HIGH TECK PRODUCTS
PO BOX 24631
WEST PALM BEACH, FLORIDA 33416
USA
877-900-8325
info@highteckproducts.com
- **Information department:** Product safety department
- **Emergency telephone number:** 800 424-9300 (Chemtrec)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2
H373 May cause damage to the hearing organs through prolonged or repeated exposure.

GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene
toluene
ethylbenzene

- **Hazard statements**

Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to the hearing organs through prolonged or repeated exposure.

- **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 2)

- **HMIS-ratings (scale 0 - 4)**

| | | |
|------------|---|----------------|
| HEALTH | 2 | Health = *2 |
| FIRE | 3 | Fire = 3 |
| REACTIVITY | 0 | Reactivity = 0 |

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

| | | |
|-----------|---|---------|
| 98-56-6 | 4-chloro-alpha,alpha,alpha-trifluorotoluene | 25-50% |
| 67-64-1 | acetone | 10-25% |
| 123-86-4 | n-butyl acetate | 2.5-10% |
| 1330-20-7 | xylene | 2.5-10% |
| 110-43-0 | heptan-2-one | 2.5-10% |
| 100-41-4 | ethylbenzene | ≤2.5% |
| | DPP Red C.I Pigment 254 | ≤2.5% |
| 108-88-3 | toluene | ≤2.5% |
| 119-64-2 | 1,2,3,4-tetrahydronaphthalene | ≤2.5% |

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 3)

- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

| | | |
|-------------|--|-------------------------|
| 67-64-1 | acetone | 200 ppm |
| 123-86-4 | n-butyl acetate | 5 ppm |
| 1330-20-7 | xylene | 130 ppm |
| 110-43-0 | heptan-2-one | 150 ppm |
| 100-41-4 | ethylbenzene | 33 ppm |
| 71-36-3 | butan-1-ol | 60 ppm |
| 108-88-3 | toluene | 67 ppm |
| 112926-00-8 | Precipitated silica (Silica-Amorphous) | 18 mg/m ³ |
| 119-64-2 | 1,2,3,4-tetrahydronaphthalene | 1.6 ppm |
| 123-42-2 | 4-hydroxy-4-methylpentan-2-one | 150 ppm |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 50 ppm |
| 108-38-3 | m-xylene | 130 ppm |
| 122-99-6 | 2-phenoxyethanol | 1.5 ppm |
| 7664-38-2 | phosphoric acid | 3 mg/m ³ |
| 14808-60-7 | Quartz (SiO ₂) | 0.075 mg/m ³ |
| 57-55-6 | Propylene glycol | 30 mg/m ³ |
| 78-83-1 | butanol | 150 ppm |

· **PAC-2:**

| | | |
|-----------|-----------------|-----------|
| 67-64-1 | acetone | 3200* ppm |
| 123-86-4 | n-butyl acetate | 200 ppm |
| 1330-20-7 | xylene | 920* ppm |
| 110-43-0 | heptan-2-one | 670 ppm |
| 100-41-4 | ethylbenzene | 1100* ppm |
| 71-36-3 | butan-1-ol | 800 ppm |

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 4)

| | | |
|-------------|--|-------------------------|
| 108-88-3 | toluene | 560 ppm |
| 112926-00-8 | Precipitated silica (Silica-Amorphous) | 200 mg/m ³ |
| 119-64-2 | 1,2,3,4-tetrahydronaphthalene | 17 ppm |
| 123-42-2 | 4-hydroxy-4-methylpentan-2-one | 350 ppm |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 1,000 ppm |
| 108-38-3 | m-xylene | 920 ppm |
| 122-99-6 | 2-phenoxyethanol | 16 ppm |
| 7664-38-2 | phosphoric acid | 30 mg/m ³ |
| 14808-60-7 | Quartz (SiO ₂) | 33 mg/m ³ |
| 57-55-6 | Propylene glycol | 1,300 mg/m ³ |
| 78-83-1 | butanol | 1,300 ppm |

· PAC-3:

| | | |
|-------------|--|-------------------------|
| 67-64-1 | acetone | 5700* ppm |
| 123-86-4 | n-butyl acetate | 3000* ppm |
| 1330-20-7 | xylene | 2500* ppm |
| 110-43-0 | heptan-2-one | 4000* ppm |
| 100-41-4 | ethylbenzene | 1800* ppm |
| 71-36-3 | butan-1-ol | 8000** ppm |
| 108-88-3 | toluene | 3700* ppm |
| 112926-00-8 | Precipitated silica (Silica-Amorphous) | 1,200 mg/m ³ |
| 119-64-2 | 1,2,3,4-tetrahydronaphthalene | 100 ppm |
| 123-42-2 | 4-hydroxy-4-methylpentan-2-one | 2100* ppm |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 5000* ppm |
| 108-38-3 | m-xylene | 2500* ppm |
| 122-99-6 | 2-phenoxyethanol | 97 ppm |
| 7664-38-2 | phosphoric acid | 150 mg/m ³ |
| 14808-60-7 | Quartz (SiO ₂) | 200 mg/m ³ |
| 57-55-6 | Propylene glycol | 7,900 mg/m ³ |
| 78-83-1 | butanol | 8000* ppm |

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: Store in a cool location.

· Information about storage in one common storage facility: Not required.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 5)

- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm
 REL Long-term value: 590 mg/m³, 250 ppm
 TLV Short-term value: 500 ppm
 Long-term value: 250 ppm
 A4, BEI

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm
 REL Short-term value: 950 mg/m³, 200 ppm
 Long-term value: 710 mg/m³, 150 ppm
 TLV Short-term value: 150 ppm
 Long-term value: 50 ppm

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm
 REL Short-term value: 655 mg/m³, 150 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV Long-term value: 20 ppm
 BEI, A4

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm
 REL Long-term value: 465 mg/m³, 100 ppm
 TLV Long-term value: 50 ppm

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm
 REL Short-term value: 545 mg/m³, 125 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV Long-term value: 20 ppm
 OTO, BEI, A3

108-88-3 toluene

PEL Long-term value: 200 ppm
 Ceiling limit value: 300; 500* ppm
 *10-min peak per 8-hr shift

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 6)

| | |
|-----|---|
| REL | Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm |
| TLV | Long-term value: 20 ppm BEI, OTO, A4 |

· Ingredients with biological limit values:

67-64-1 acetone

| | |
|-----|--|
| BEI | 25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) |
|-----|--|

1330-20-7 xylene

| | |
|-----|--|
| BEI | 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids |
|-----|--|

100-41-4 ethylbenzene

| | |
|-----|---|
| BEI | 0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific) |
|-----|---|

108-88-3 toluene

| | |
|-----|--|
| BEI | 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene |
| | 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene |
| | 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) |

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 7)

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Color: Red

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined (pH N/A in solvent coatings)

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 55.8-56.6 °C (132.4-133.9 °F)

- **Flash point:** <-18 °C (<-0.4 °F)

- **Flammability (solid, gaseous):** Highly flammable.

- **Auto igniting:** 370 °C (698 °F)

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

Lower: 2.6 Vol %

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 8)

| | |
|---|--|
| Upper: | 13 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 233 hPa (174.8 mm Hg) |
| · Vapor pressure at 50 °C (122 °F): | 800 hPa (600 mm Hg) |
| · Density at 20 °C (68 °F): | 1.139 g/cm ³ (9.505 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Fully miscible. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 30.0 % |
| VOC content: | 19.13 % |
| | 398.4 g/l / 3.32 lb/gal |
| · Solids content: | 28.5 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

| | |
|---|--|
| · IARC (International Agency for Research on Cancer) | |
|---|--|

| | |
|---------|---|
| 98-56-6 | 4-chloro-alpha,alpha,alpha-trifluorotoluene |
|---------|---|

2B

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 9)

| | | |
|-------------|--|----|
| 1330-20-7 | xylene | 3 |
| 100-41-4 | ethylbenzene | 2B |
| 108-88-3 | toluene | 3 |
| 112926-00-8 | Precipitated silica (Silica-Amorphous) | 3 |
| 95-47-6 | o-xylene | 3 |
| 106-42-3 | p-xylene | 3 |
| 108-38-3 | m-xylene | 3 |
| 14808-60-7 | Quartz (SiO ₂) | 1 |

· **NTP (National Toxicology Program)**

| | | |
|------------|----------------------------|---|
| 14808-60-7 | Quartz (SiO ₂) | K |
|------------|----------------------------|---|

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1263

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 10)

- **UN proper shipping name**
- **DOT**
- **IMDG, IATA**

Paint
PAINT

- **Transport hazard class(es)**
- **DOT**



- **Class**
- **Label**

3 Flammable liquids
3

- **IMDG, IATA**



- **Class**
- **Label**

3 Flammable liquids
3

- **Packing group**
- **DOT, IMDG, IATA**

II

- **Environmental hazards:**

Not applicable.

- **Special precautions for user**
- **Hazard identification number (Kemler code):**
- **EMS Number:**
- **Stowage Category**

Warning: Flammable liquids
33
F-E, S-E
B

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

- **Transport/Additional information:**

- **DOT**
- **Quantity limitations**

On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

- **IMDG**
- **Limited quantities (LQ)**
- **Excepted quantities (EQ)**

5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **UN "Model Regulation":**

UN 1263 PAINT, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

(Contd. on page 12)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 11)

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

100-41-4 ethylbenzene

71-36-3 butan-1-ol

108-88-3 toluene

95-47-6 o-xylene

106-42-3 p-xylene

108-38-3 m-xylene

122-99-6 2-phenoxyethanol

7664-38-2 phosphoric acid

· TSCA (Toxic Substances Control Act):

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

ACTIVE

67-64-1 acetone

ACTIVE

123-86-4 n-butyl acetate

ACTIVE

9004-36-8 Cellulose Acetate Butyrate

ACTIVE

1330-20-7 xylene

ACTIVE

110-43-0 heptan-2-one

ACTIVE

100-41-4 ethylbenzene

ACTIVE

DPP Red C.I Pigment 254

ACTIVE

71-36-3 butan-1-ol

ACTIVE

108-88-3 toluene

ACTIVE

119-64-2 1,2,3,4-tetrahydronaphthalene

ACTIVE

123-42-2 4-hydroxy-4-methylpentan-2-one

ACTIVE

108-65-6 2-methoxy-1-methylethyl acetate

ACTIVE

64742-95-6 Solvent naphtha (petroleum), light arom.

ACTIVE

95-47-6 o-xylene

ACTIVE

106-42-3 p-xylene

ACTIVE

108-38-3 m-xylene

ACTIVE

64742-47-8 Distillates (petroleum), hydrotreated light

ACTIVE

122-99-6 2-phenoxyethanol

ACTIVE

8002-74-2 Paraffin waxes and Hydrocarbon waxes

ACTIVE

7664-38-2 phosphoric acid

ACTIVE

14808-60-7 Quartz (SiO₂)

ACTIVE

57-55-6 Propylene glycol

ACTIVE

78-83-1 butanol

ACTIVE

· Hazardous Air Pollutants

1330-20-7 xylene

100-41-4 ethylbenzene

108-88-3 toluene

95-47-6 o-xylene

106-42-3 p-xylene

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 12)

108-38-3 m-xylene

- **Proposition 65**

- **Chemicals known to cause cancer:**

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

100-41-4 ethylbenzene

14808-60-7 Quartz (SiO₂)

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

67-64-1 acetone

I

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

71-36-3 butan-1-ol

D

108-88-3 toluene

II

95-47-6 o-xylene

I

106-42-3 p-xylene

I

108-38-3 m-xylene

I

- **TLV (Threshold Limit Value)**

67-64-1 acetone

A4

1330-20-7 xylene

A4

100-41-4 ethylbenzene

A3

108-88-3 toluene

A4

95-47-6 o-xylene

A4

106-42-3 p-xylene

A4

108-38-3 m-xylene

A4

14808-60-7 Quartz (SiO₂)

A2

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7 Quartz (SiO₂)

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word Danger**

- **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene

(Contd. on page 14)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 13)

toluene

ethylbenzene

- **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to the hearing organs through prolonged or repeated exposure.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

- **Contact:** Product Safety Dept.

- **Date of preparation / last revision** 02/27/2024

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 15)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: HFP451C 3.5 VOC CORVETTE RED GM WA-9075 B/C

(Contd. of page 14)

*vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flammable Liquids 2: Flammable liquids – Category 2**Skin Irritation 2: Skin corrosion/irritation – Category 2**Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A**Carcinogenicity 2: Carcinogenicity – Category 2**Toxic to Reproduction 2: Reproductive toxicity – Category 2**Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2**** Data compared to the previous version altered.**

USA